

NEXT GENERATION OF DESKTOP PRINTERS

With superior performance and affordable price, these 2", 203 or 305 dpi, Direct Thermal/Thermal Transfer printers are best in their class.

The SATO CG Series models are delivered stock out of the box with competitive emulations on board, optimal interfaces (built in USB standard) and an anti-microbial casing for outstanding performance in clinical and processing environments.



PRINT SPECIFICATIONS

Print Method: Direct Thermal / Thermal Transfer

Print Resolution: 203 or 305 dpi

Print width: 56 mm- 2.2"

Print speed: 101 mm/s- 4 inch per second

Emulations: ZPL- EPL

Interfaces: USB - RS232C - USB - LAN

Media Width: 12 mm to 60 mm 0.47" to 2.36"

FEATURES

- Quick and Efficient Setup
- Easy to Use
- Multiple Connections
- Compact Design
- Quality Label Printing
- Compact Design
- Anti- Microbial Casing

AVAILABLE FROM
£321.00 EX.VAT



CONSUMABLES

Sensor Type: I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive)

Media Type: Roll or fan-fold die cut labels, Plain paper face stock, Synthetics and Continuous stock

Media Thickness: 0.06 – 0.19mm (0.002" – 0.007"

Label Shape: Max. outside diameter: Ø 130mm (5.12"), Core diameter: Ø 25.4mm (1") or Ø 38.1mm (1.5")

Ribbon: Width: 59mm (2.32") Max. Length: 100m (328')

FONT / SYMBOLOGIES

Fonts: Bitmap Fonts Alphanumerical and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)

Barcode: UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC

Print Rotation: 0°, 90°, 180°, 270°

OPERATING CHARACTERISTICS

Power Requirements: Input voltage adapter: AC100V-240V (auto switching)/40W (peak) – Input voltage printer: 19V/3A

Environment: Operating 0 – 35°C / 30 – 80% RH (without condensation)
Storage -10 – 60°C / 15 – 85% RH (without condensation)

Dimension: (W x D x H): 128 x 235 x 173mm (5.04" x 9.25" x 6.81")

Weight: TT model (approx 1.6 kg / 3.5 lbs), DT model (approx 1.5 kg / 3.3 lbs)

MISCELLANEOUS

Certifications: FCC, UL, CSA, CCC, CE, ROHS compliant, Energy Star™

Anti-microbial Finishing: The material of the casing includes an anti-microbial substance which is tested according to the JISZ2801 standard
The anti-microbial casing discourages the growth of bacteria and micro-organisms

OPTIONS

Accessories: Cutter, Dispenser, RFID HF Kit 13,56Mhz, SATO Keypad, Unwinder, NiceLabel